



EN AW-5052 [AlMg2,5]

d	l <sup>+1</sup>	$\frac{d}{k}$		
<b>3,2</b>	6,8	0,8 - 3,4		500
	8,0	0,8 - 4,8		500
	9,5	1,2 - 6,4		500
	11,0	4,0 - 7,9		500
<b>dk</b> 6,4	<b>dm</b> 1,8	<b>k</b> 1,0	3,3 mm    720 N    1000 N	
<b>4,0</b>	6,0	0,5 - 3,0		500
	9,5	1,2 - 6,4		500
	12,7	4,0 - 9,5		500
	16,9	6,4 - 12,7		500
<b>dk</b> 7,9	<b>dm</b> 2,3	<b>k</b> 1,2	4,1 mm    1120 N    1650 N	

d	l <sup>+1</sup>	$\frac{d}{k}$		
<b>4,8</b>	10,3	1,6 - 6,4		500
	15,1	4,8 - 11,1		500
	16,9	6,4 - 12,7		500
	20,0	10,0 - 16,0		500
	24,8	12,7 - 19,8		500
	30,0	19,0 - 24,0		500
<b>dk</b> 9,8	<b>dm</b> 2,8	<b>k</b> 1,5	4,9 mm    1530 N    2300 N	